



Product Data

Product Code	ARX-511
Type	Surface mounted grazing light
Construction	CNC machined brass
Warranty	10 Years
Available Finishes	Aged Brass, Natural Brass, Brushed Copper, Electroless Nickel

Electrical Data

Input Voltage	24VDC
Nominal Power	2W
Dimming	Yes. 2-Wire direct dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	60mm x 90mm x 18mm
Weight	0.310 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Diffuse optic)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	99	111	117	125
Efficacy (lm/W)	57	64	67	72
CRI (Ra)	90+	90+	90+	90+

Optical Data (3000K)

Description	Diffuse (DF)
Nominal FWHM	65
Peak Intensity (cd/lm)	89
UGR	-

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

PIA 60 is a compact wall grazing light with a pool safe non climbable sloped face. Available with low-glare, High CRI light source. IP65 protection

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.



10Y
Years
Warranty



IP65
Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



24V
DC
Observe
Polarity



LM80
Lumen
Maintenance

Aged Brass, Waxed



Natural Brass, Waxed



Brushed Copper



Electroless Nickel



Dimensions

