

**Product Data**

Product Code	ARX-512
Type	Surface mounted grazing light
Construction	CNC machined brass
Warranty	10 Years

Electrical Data

Input Voltage	24VDC
Nominal Power	4W
Dimming	Yes, 2-Wire direct dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	90mm x 90mm x 18mm
Weight	0.310 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Diffuse optic)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	215	240	253	270
Efficacy (lm/W)	63	70	74	79
CRI (Ra)	90+	90+	90+	90+

Optical Data (3000K)

Description	Diffuse
Nominal FWHM	68
Peak Intensity (cd/lm)	175
UGR	-

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

PIA 90 is a wall grazing light with a pool safe non climbable sloped face. Available with low-glare, High CRI light source. IP65 protection

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.



Years
Warranty



Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



Observe
Polarity



Lumen
Maintenance

DRAFT DATASHEET

arx.lighting has full product details and all available options, order code configuration & customised datasheets.

for sales enquiries, visit estlighting.com.au

Natural Brass, Waxed



Carbonite Aged, Waxed



Dimensions

