

PIA SLIM / ARX-517

Slimline surface grazing light





Product Code	ARX-517				
Туре	Slimline surface grazing light				
Construction	CNC machined brass				
Warranty	10 Years				
Available Finishes	Aged Brass, Natural Brass, Brushed Coppe Electroless Nickle				
Electrical Data					
nput Voltage	24VDC				
Nominal Power	2W	2W			
Dimming	Yes. 2-Wi	Yes. 2-Wire direct dimming.			
Wiring	Parallel				
Mechanical & Thermal Data					
Overall Dimensions	180mm x 35mm x 18mm				
Weight	0.310 kg				
Max Ambient Temperature	40°C				
ID D I'	IP65				
IP Rating	1700				
Photometric Data (Narrow Med					
		2700K	3000K	4000K	
Photometric Data (Narrow Med	dium optic)	2700K 124	3000K	4000K	
Photometric Data (Narrow Med	dium optic)				
Photometric Data (Narrow Med CCT Rated Flux (Im delivered)	dium optic)	124	131	140	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W)	dium optic)	124 59	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra)	dium optic)	124 59	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra) Optical Data (3000K)	2200K	124 59	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra) Optical Data (3000K)	dium optic) 2200K - - Diffuse	124 59	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra) Optical Data (3000K) Description Nominal FWHM	dium optic) 2200K - - - Diffuse 86	124 59	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra) Optical Data (3000K) Description Nominal FWHM Peak Intensity (cd/Im)	2200K - -	124 59	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra) Optical Data (3000K) Description Nominal FWHM Peak Intensity (cd/Im)	2200K - -	124 59	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra) Optical Data (3000K) Description Nominal FWHM Peak Intensity (cd/Im) UGR	2200K - -	124 59 90+	131	140 66	
Photometric Data (Narrow Med CCT Rated Flux (Im delivered) Efficacy (Im/W) CRI (Ra) Optical Data (3000K) Description Nominal FWHM Peak Intensity (cd/Im) UGR Lifetime & Compliance Data L70 / B10	Diffuse 86 71 - 50,000h	124 59 90+	131	140 66	

Introduction

PIA SLIM is a low profile linear grazing light suitable for stair risers and other way finding applications. With an innovative bracket that houses the light source, PIA SLIM is easy to install low to the ground.

Integrated 24V PWM 2-wire light sources are achieved via the development of custom COB modules, all feature 90+ CRI and chemically etched glass for perfectly diffuse light output.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.













Years Warranty

s Ingress anty Protection

Solvent Resistant

Saltwater Resistant

Observe Lumen Polarity Maintenance



PIA SLIM / ARX-517

Dimensions and finish options

Aged Brass, Waxed

Natural Brass, Waxed





Brushed Copper

Electroless Nickle





Dimensions

