



Product Data

Product Code	ARX-536
Type	Compact hooded recessed uplight
Construction	CNC machined brass
Warranty	10 Years

Electrical Data

Input Voltage	24VDC
Nominal Power	2W
Dimming	Yes. 3-Wire PWM Signal dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	60mm x 55mm
Weight	0.610 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Narrow Medium optic)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	185	195	209
Efficacy (lm/W)	-	48	51	55
CRI (Ra)	-	90+	90+	90+

Optical Data (3000K)

Description	Spot	Narrow Medium	Wide	Full Flood	ASYM
Nominal FWHM	16	27	48	75	-
Peak Intensity (cd/lm)	1478	472	213	143	230
UGR	-	-	-	-	-

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

ALY is a compact cut-off uplight with shallow recess and asymmetrical optics. Perfect for wall washing or offset illumination of features and flora, ALY is available in our natural tumbled and waxed finish or the sophisticated carbonite aged brass.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.



10Y
Years
Warranty



IP65
Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



24V
DC
Observe
Polarity



LM80
Lumen
Maintenance

PRELIMINARY DATASHEET

Natural Brass, Waxed



Carbonite Aged, Waxed



Dimensions

