



Product Data

Product Code	ARX-537
Type	Compact, low-glare recessed uplight
Construction	CNC machined brass
Warranty	10 Years
Available Finishes	Aged Brass, Natural Brass, Brushed Copper, Electroless Nickel

Electrical Data

Input Voltage	24VDC
Nominal Power	4W
Dimming	Yes. 3-Wire PWM Signal dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	54mm x 75mm
Weight	0.5 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Narrow Medium optic)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	184	194	208
Efficacy (lm/W)	-	47	50	53
CRI (Ra)	-	90+	90+	90+

Optical Data (3000K)

Description	Narrow	Medium
Nominal FWHM	28	40
Peak Intensity (cd/lm)	877	427
UGR	TBC	TBC

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

VOY is a compact uplight with a deep recessed light source that delivers ultra-low glare uplighting to columns, walls and features.

With integral glare control and high-performance optics, VOY can achieve higher efficiencies and superior optical effects compared to the use of traditional honeycomb louvres.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.



10Y
Years
Warranty



IP65
Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



24V
DC
Observe
Polarity



LM80
Lumen
Maintenance

Aged Brass, Waxed



Natural Brass, Waxed



Brushed Copper



Electroless Nickel



Dimensions

