



DRAFT DATASHEET

Product Data

Product Code	ARX-720
Type	Mini adjustable spike spot
Construction	CNC machined brass
Warranty	10 Years

Electrical Data

Input Voltage	24VDC
Nominal Power	2W / 4W
Dimming	Yes. 3-Wire PWM Signal dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	20mm x 295mm
Weight	0.250 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Narrow Medium optic)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	?	?	?
Efficacy (lm/W)	-	?	?	?
CRI (Ra)	-	90+	90+	90+

Optical Data (3000K)

Description	Narrow Spot	Medium	Medium Wide	Wide
Nominal FWHM	12	28	42	62
Peak Intensity (cd/lm)	?	?	?	?
UGR	-	-	-	-

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

LUMI delivers optimised output and glare control in a minimal, low-impact form factor. With it's 20mm profile, LUMI is perfect for smaller spaces and lifestyle projects including balconies and formal gardens.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.



10Y
Years
Warranty



IP65
Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



24V
DC
Observe
Polarity



LM80
Lumen
Maintenance

Natural Brass, Waxed



Carbonite Aged, Waxed



Dimensions

