







Product Code	ARX-720				
Туре	Mini adjustable spike spot				
Construction	CNC machined brass				
Warranty	10 Years				
Available Finishes	Aged Brass, Natural Brass, Brushed Coppe Electroless Nickle				
Electrical Data					
Input Voltage	24VDC				
Nominal Power	2W / 4W	2W / 4W			
Dimming	Yes. 3-Wire	Yes. 3-Wire PWM Signal dimming.			
Wiring	Parallel	Parallel			
Mechanical & Thermal Data					
Overall Dimensions	20mm x 29	20mm x 295mm			
Weight	0.250 kg	0.250 kg			
Max Ambient Temperature	40°C	40°C			
IP Rating	IP65	IP65			
Photometric Data (Narrow Med	dium optic)				
CCT	2200K	2700K	3000K	4000K	
Rated Flux (Im delivered)	-	?	?	?	
Efficacy (lm/W)	-	?	?	?	
CRI (Ra)	-	90+	90+	90+	
Optical Data (3000K)					
Description	Narrow Spot	Medium	Medium Wide	Wide	
Nominal FWHM	12	28	42	62	
Dool Intensity (ad/lm)	?	?	?	?	
Peak Intensity (cd/lm)					
UGR	-	-			
* * * * * * * * * * * * * * * * * * * *	-	-	-		
UGR	- 50,000h	-			
UGR Lifetime & Compliance Data	- 50,000h Complian	t			
UGR Lifetime & Compliance Data L70 / B10			-		

## Introduction

LUMI delivers optimised output and glare control in a minimal, low-impact form factor. With it's 20mm profile, LUMI is perfect for smaller spaces and lifestyle projects including balconies and formal gardens.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.













rears Warranty

Ingress Protection

Solvent Resistant

Saltwater Resistant

Observe Polarity

Lumen Maintenance



## Aged Brass, Waxed



## Natural Brass, Waxed



**Brushed Copper** 



**Electroless Nickle** 



## Dimensions

