



Product Data

Product Code	ARX-745
Type	Path light
Construction	CNC machined brass
Warranty	10 Years

Electrical Data

Input Voltage	24VDC
Nominal Power	4W
Dimming	Yes. 3-Wire PWM Signal dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	40mm x 400mm
Weight	0.500 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Narrow Medium optic)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	200	210	-
Efficacy (lm/W)	-	-	-	-
CRI (Ra)	-	90+	90+	90+

Optical Data (3000K)

Description	Medium	Wide
Nominal FWHM	28	50
Peak Intensity (cd/lm)	TBC	TBC
UGR	-	-

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

PEEK is a unique wayfinding luminaire, suitable for pathlighting or other applications requiring a subtle offset effect from a minimal fitting.

Featuring a custom engineered flush-fit acrylic shield with integral glare and optical control, PEEK is an advanced light fitting that is perfect for both modern and traditional settings.

PEEK is currently in development and will be available Q4/2024

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.

PRELIMINARY DATASHEET



Years
Warranty



Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



Observe
Polarity



Lumen
Maintenance

Natural Brass, Waxed



Carbonite Aged, Waxed



Dimensions

