



#### Product Data

Product Code	ARX-753
Type	Low glare adjustable surface spot
Construction	CNC machined brass
Warranty	10 Years

#### Electrical Data

Input Voltage	24VDC
Nominal Power	4W / 6W / <b>8W</b>
Dimming	Yes. 3-Wire PWM Signal dimming.
Wiring	Parallel

#### Mechanical & Thermal Data

Overall Dimensions	100mm x 50mm x 71mm
Weight	1.0 kg
Max Ambient Temperature	40°C
IP Rating	IP65

#### Photometric Data (Medium optic, 8W)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	689	728	778
Efficacy (lm/W)	-	83	87	93
CRI (Ra)	-	90+	90+	90+

#### Optical Data (3000K)

Description	Narrow Spot	Spot	Medium	Wide
Nominal FWHM	15	22	34	53
Peak Intensity (cd/lm)	8676	4539	2303	865
UGR	-	-	-	-

#### Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

#### Introduction

TULA POS is a minimal, posable surface mount spot light suitable for walls and posts.

With a 50D profile, integrated low-glare optics and a unique adjustment mechanism, the TULA range is perfect for a large variety of architectural lighting tasks.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from [arx.lighting](http://arx.lighting).



Years  
Warranty



Ingress  
Protection



Solvent  
Resistant



Saltwater  
Resistant



Observe  
Polarity



Lumen  
Maintenance

## Natural Brass, Waxed



## Carbonite Aged, Raw



## Dimensions

