



Product Data

Product Code	ARX-753
Type	Low glare adjustable surface spot
Construction	CNC machined brass
Warranty	10 Years
Available Finishes	Aged Brass, Natural Brass, Brushed Copper, Electroless Nickel

Electrical Data

Input Voltage	24VDC
Nominal Power	4W / 6W / 8W
Dimming	Yes. 3-Wire PWM Signal dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	100mm x 50mm x 71mm
Weight	1.0 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Medium optic, 8W)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	689	728	778
Efficacy (lm/W)	-	83	87	93
CRI (Ra)	-	90+	90+	90+

Optical Data (3000K)

Description	Narrow Spot	Spot	Medium	Wide
Nominal FWHM	15	22	34	53
Peak Intensity (cd/lm)	8676	4539	2303	865
UGR	-	-	-	-

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

TULA POS is a minimal, posable surface mount spot light suitable for walls and posts.

With a 50D profile, integrated low-glare optics and a unique adjustment mechanism, the TULA range is perfect for a large variety of architectural lighting tasks.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.



Years
Warranty



Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



Observe
Polarity



Lumen
Maintenance

Aged Brass, Waxed



Natural Brass, Waxed



Brushed Copper



Electroless Nickel



Dimensions

