



Product Data

Product Code	ARX-754
Type	Twin posable surface mount light
Construction	CNC machined brass
Warranty	10 Years

Electrical Data

Input Voltage	24VDC
Nominal Power	16W (8+8)
Dimming	Yes. 3-Wire PWM Signal dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	50mm x 100mm
Weight	1.9 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Medium optic, single output)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	689+689	728+728	778+778
Efficacy (lm/W)	-	83	87	93
CRI (Ra)	-	90+	90+	90+

Optical Data (3000K)

Description	Narrow Spot	Spot	Medium	Wide
Nominal FWHM	15	22	34	53
Peak Intensity (cd/lm)	8676	4539	2303	865
UGR	-	-	-	-

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

TULA TWIN is a minimal, posable surface mount spot light suitable for walls and posts.

With a 50D profile, integrated low-glare optics and a unique adjustment mechanism, the TULA range is perfect for a large variety of architectural lighting tasks.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.

PRELIMINARY DATASHEET



Years
Warranty



Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



Observe
Polarity



Lumen
Maintenance

Natural Brass, Waxed



Carbonite Aged, Waxed



Dimensions

