



Product Data

Product Code	ARX-770
Type	Hooded surface grazing light
Construction	CNC machined brass
Warranty	10 Years
Available Finishes	Aged Brass, Natural Brass, Brushed Copper, Electroless Nickel

Electrical Data

Input Voltage	24VDC
Nominal Power	2W
Dimming	Yes. 2-Wire direct dimming.
Wiring	Parallel

Mechanical & Thermal Data

Overall Dimensions	70mm
Weight	0.350 kg
Max Ambient Temperature	40°C
IP Rating	IP65

Photometric Data (Narrow Medium optic)

CCT	2200K	2700K	3000K	4000K
Rated Flux (lm delivered)	-	140	150	160
Efficacy (lm/W)	-	-	-	-
CRI (Ra)	-	90+	90+	90+

Optical Data (3000K)

Description	Diffuse
Nominal FWHM	-
Peak Intensity (cd/lm)	TBC
UGR	TBC

Lifetime & Compliance Data

L70 / B10	50,000h
EMI	Compliant
RCM	Approved
Mercury Content	0mg

Introduction

PEBL is a new take on a classic function, providing an updated look while still delivering optimal performance and optical control.

Perfect for wayfinding, grazing or step light applications PEBL features an integrated surface mounting bracket.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.



Years
Warranty



Ingress
Protection



Solvent
Resistant



Saltwater
Resistant



Observe
Polarity



Lumen
Maintenance

Aged Brass, Waxed



Natural Brass, Waxed



Brushed Copper



Electroless Nickel



Dimensions

