





Product Data					
Product Code	ARX-860				
Туре	Surface mount downlight				
Construction	CNC machined brass				
Warranty	10 Years				
Available Finishes	Aged Brass, Natural Brass, Brushed Copper, Electroless Nickle				
Electrical Data					
Input Voltage	24VDC	24VDC			
Nominal Power	8W				
Dimming	Yes. 3-Wire	Yes. 3-Wire PWM Signal dimming.			
Wiring	Parallel				
Mechanical & Thermal Data					
Overall Dimensions	60mm x 100mm				
Weight	0.850 kg	0.850 kg			
Max Ambient Temperature	40°C				
IP Rating	IP65				
Photometric Data (Medium opti	c, 8W)				
CCT	2200K	2700K	3000K	4000K	
Rated Flux (Im delivered)	-	577	610	652	
Efficacy (lm/W)	-	84	88	94	
CRI (Ra)	-	90+	90+	90+	
Optical Data (3000K)					
Description	Narrow Spot	Spot	Medium	Wide	
Nominal FWHM	12	20	35	50	
Peak Intensity (cd/lm)	6390	4067	1703	1003	
UGR	-	-	-	-	
Lifetime & Compliance Data					
L70 / B10	50,000h				
EMI	Compliant				
RCM	Approved				
Mercury Content	0mg				

Introduction

JUNI is a minimal surface downlight can, available with low-glare optics, IP65 protection and a high-CRI light source.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.













Ingress Protection

Resistant

Resistant

Polarity Maintenance



JUNI SOLO / ARX-860

Dimensions and finish options

Aged Brass, Waxed







Brushed Copper

Electroless Nickle





Dimensions

