





Product Data					
Product Code	ARX-862				
Туре	Surface m	Surface mount wall up/down light			
Construction	CNC machined brass				
Warranty	10 Years				
Available Finishes		Aged Brass, Natural Brass, Brushed Copper, Electroless Nickle			
Electrical Data					
Input Voltage	24VDC	24VDC			
Nominal Power	16W (8+8)	16W (8+8)			
Dimming	Yes. 3-Wire	Yes. 3-Wire PWM Signal dimming.			
Wiring	Parallel	Parallel			
Mechanical & Thermal Data					
Overall Dimensions	60mm x 18	60mm x 180mm x 85mm			
Weight	1.85 kg	1.85 kg			
Max Ambient Temperature	40°C	40°C			
IP Rating	IP65	IP65			
Photometric Data (Medium opt	ic, 8W+8W)				
CCT	2200K	2700K	3000K	4000K	
Rated Flux (Im delivered)	-	577+577	610+610	652+652	
Efficacy (Im/W)	-	84	88	94	
CRI (Ra)	-	90+	90+	90+	
Optical Data (3000K)					
Description	Narrow Spot	Spot	Medium	Wide	
Nominal FWHM	12	20	35	50	
Peak Intensity (cd/lm)	6390	4067	1703	1003	
UGR	-	-	-	-	
Lifetime & Compliance Data					
L70 / B10	55,000h	55,000h			
EMI	Complian	Compliant			
RCM	Approved	Approved			
Mercury Content	0mg	0mg			

Introduction

JUNI DUO is an up/down, bi-directional fixed wall light available with low-glare optics, IP65 protection and a high-CRI light source.

Crafted from solid brass, the ARX range is 100% Australian made in Sydney.

Full IES files, LM-80 and compliance data is available from arx.lighting.













Ingress Warranty

Protection

Resistant

Resistant Polarity

Maintenance



JUNI DUO / ARX-862

Dimensions and finish options

Aged Brass, Waxed



Natural Brass, Waxed



Brushed Copper



Electroless Nickle



Dimensions

